

Construction Products Regulation - Declaration of Performance

Reference No:

AP001

| | |
|--|---|
| 1. Identification code: | Cationic bituminous emulsion Ayton C40B4 |
| 2. Notified Body / Certificate number: | BSI / 0086-CPR-598865 |
| 3. Intended use: | Tack coat |
| 4. Manufacturer | Ayton Products (a trading name of Kier Integrated Services Limited) Browick Road Wymondham Norfolk NR18 0RJ |
| 5. Authorised representative | Not applicable |
| 6. Assessment and verification of constancy of performance | 2+ |
| 7. Relevant harmonised standard | EN 13808:2013 |
| 8. European Technical Assessment | Not applicable |
| 9. Declared Performance | |

Essential Characteristic

Declared Performance

Standard

| Essential Characteristic | Declared Performance | Standard |
|--|--------------------------|-------------------------|
| Cationic bituminous emulsion: C40B4 to EN 13808:2013 | | |
| Viscosity (dynamic) | ≤ 30 mPa.s (Class 9) | EN 13302 |
| Water effect on binder adhesion | NR (Class 0) | EN 13614 |
| Breaking behaviour | 110 - 195 (Class 4) | EN 13075-1 (Forshammar) |
| Dangerous substances | NPD | - |
| Residual binder recovered by evaporation from cationic bituminous emulsion according to EN 13074-1 | | |
| Consistency at intermediate service temperature | ≤ 220 x 0.1 mm (Class 5) | EN 1426 |
| Consistency at elevated service temperature | ≥ 35 °C (Class 8) | EN 1427 |
| Cohesion | NR (Class 0) | EN 13588 |
| Durability Stage 1 Binder recovered by evaporation (EN 13074-1) and subjected to stabilisation (EN 13074-2) | | |
| Durability of consistency at intermediate service temperature | ≤ 220 x 0.1 mm (Class 5) | EN 1426 |
| Durability of consistency at elevated service temperature | ≥ 35 °C (Class 8) | EN 1427 |
| Durability of cohesion | NR (Class 0) | EN 13588 |



Construction Products Regulation - Declaration of Performance

| Durability Stage 2 Binder recovered by evaporation (EN 13074-1) and subjected to stabilisation (EN 13074-2) and ageing (EN 14769) | | |
|--|--------------|----------|
| Durability of consistency at intermediate service temperature | NPD | EN 1426 |
| Durability of consistency at elevated service temperature | NPD | EN 1427 |
| Durability of cohesion | NR (Class 0) | EN 13588 |

Specific Technical Documentation

Not applicable

- 10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Signature:



Date: 04th June 2018

**Stephen Collins
Operations Manager
Ayton Products
Kier Integrated Services Limited
Tempsford Hall
Sandy
Bedfordshire
SG19 2BD**