

Colourchip© Coated Chippings

Description

Colourchip© resin coated chippings are the simple way to create attractive and cost effective decorative finishes and eye catching colour demarcations in blacktop surfacing.

Colourchip© chippings comprise specially selected and graded aggregates coated in a bespoke clear resin which are fully compatible with bitumen based products.

The clear binder allows the Colourchip© to fully bond to the HRA while also allowing the natural colour of the aggregate to provide an immediate decorative finish which is maintained as the surface mellows and weathers.

Colourchip© coated chippings can be used in locations where a permanent coloured or decorative finish is required.

Typical Uses

- Pedestrian areas
- Driveways
- Footpaths
- Roadways
- Bus and cycle lanes
- Village gateways

Availability

Colourchip currently available as standard:

PC10 8-14mm Harden Red pigmented

PC8 14-20mm Harden Red pigmented

PC11 14-20mm Balmullo Pink clear coated

PC13 8-14mm Norfolk Gravel clear coated

PC14 14-20mm Norfolk Gravel clear coated

PC19 8-14mm Silver Grey Granite clear coated

PC22 14-20mm Silver Grey Granite clear coated

In addition Criggion Green and Harden Red clear coated are available to special order.

Supply

Colourchip© is usually supplied in 1 tonne or 25kg bags collected from our Wymondham or Cambridge depots or delivered on our transport. Large quantities can be manufactured and delivered by bulk tipper. Please check the lead time when ordering.

Rates of Spread

Colourchip© is supplied as a decorative, aesthetic enhancement to HRA and consequently the suggested spread rates to achieve an approximate 25% coverage are:

5kg per square meter for 14mm chippings

6.5kg per square meter for 20mm chippings

Application

Colourchip® coated chippings should be spread evenly over the surface and rolled into the hot asphalt at the time of laying. A correctly calibrated chipping machine can be used however hand chipping using a wide mouthed shovel is also an acceptable method of distribution.

Hot rolled asphalt to BSEN 13108-4 must not contain more than 40% of coarse aggregate to allow the Colourchip® to successfully bed into the surface.

Colourchip® is manufactured and supplied as a decorative enhancement to HRA and it is the specifiers responsibility to decide its suitability for any given location. The aggregate is graded and Colourchip® manufactured to a bespoke specification and has not been tested to comply with any highway specification.

For more information or to place an order

Tel: 01953 602002

E mail: sales@ayton.co.uk

Fax: 01953 609864

www.ayton.co.uk

Ayton Products, Browick Road, Wymondham, Norfolk, NR18 0RJ

Ayton Products is a trading name of Kier Integrated Services Limited registered in England 00873179

Registered Office: Tempsford Hall, Sandy, Bedfordshire, SG19 2BD



Balmullo



Norfolk Gravel



Silver Grey



Harden Red Pigmented

Feb 2018