



2797



BROWICK ROAD WYMONDHAM NORFOLK NR18 0RJ
TEL : 01953 602002 FAX : 01953 609864
www.ayton.co.uk sales@ayton.co.uk

13

2797-CPR-598865

Essential Characteristic	Declared Performance	Standard
Cationic bituminous emulsion: Ayton C60B5-1 C60B5 to EN 13808:2013		
Viscosity (dynamic)	20 – 300 mPa.s (Class 10)	EN 13302
Water effect on binder adhesion	NPD (Class 0)	EN 13614
Breaking behaviour	> 170 (Class 5)	EN 13075-1 (Forshammar)
Dangerous substances	NPD	-
Residual binder recovered by evaporation from cationic bituminous emulsion according to EN 13074-1		
Consistency at intermediate service temperature	≤ 150 x 0.1 mm (Class 4)	EN 1426
Consistency at elevated service temperature	≥ 43 °C (Class 6)	EN 1427
Cohesion	NR (Class 0)	EN 13588
Durability Stage 1 Binder recovered by evaporation (EN 13074-1) and subjected to stabilisation (EN 13074-2)		
Durability of consistency at intermediate service temperature	≤ 150 x 0.1 mm (Class 4)	EN 1426
Durability of consistency at elevated service temperature	≥ 43 °C (Class 6)	EN 1427
Durability of cohesion	NR (Class 0)	EN 13588
Durability Stage 2 Binder recovered by evaporation (EN 13074-1) and subjected to stabilisation (EN 13074-2) and ageing (EN 14769)		
Durability of consistency at intermediate service temperature	NPD	EN 1426
Durability of consistency at elevated service temperature	NPD	EN 1427
Durability of cohesion	NR (Class 0)	EN 13588

