

CE

2797



BROWICK ROAD WYMONDHAM NORFOLK NR18 0RJ
TEL : 01953 602002 FAX : 01953 609864
www.ayton.co.uk sales@ayton.co.uk

21

2797-CPR-598865

Essential Characteristic	Declared Performance	Standard
Cationic bituminous emulsion: Ayton Aquagrip KE92P C50BP4 to EN 13808:2013		
Viscosity (dynamic)	≤ 30 mPa.s (Class 9)	EN 13302
Water effect on binder adhesion	NPD (Class 0)	EN 13614
Breaking behaviour	110 – 195 (Class 4)	EN 13075-1 (Forshammar)
Dangerous substances	NPD	-
Residual binder recovered by evaporation from cationic bituminous emulsion according to EN 13074-1		
Consistency at intermediate service temperature	≤ 220 x 0.1 mm (Class 5)	EN 1426
Consistency at elevated service temperature	≥ 39 °C (Class 7)	EN 1427
Cohesion	≥ 1.2 J/cm ² (Class 3)	EN 13588
Durability Stage 1 Binder recovered by evaporation (EN 13074-1) and subjected to stabilisation (EN 13074-2)		
Durability of consistency at intermediate service temperature	≤ 220 x 0.1 mm (Class 5)	EN 1426
Durability of consistency at elevated service temperature	≥ 39 °C (Class 7)	EN 1427
Durability of cohesion	≥ 1.2 J/cm ² (Class 3)	EN 13588
Durability Stage 2 Binder recovered by evaporation (EN 13074-1) and subjected to stabilisation (EN 13074-2) and ageing (EN 14769)		
Durability of consistency at intermediate service temperature	NPD	EN 1426
Durability of consistency at elevated service temperature	NPD	EN 1427
Durability of cohesion	NPD	EN 13588

